DECLARATION OF PERFORMANCE
N° LRSILFEU 01A EN

LR ETANCO SAS
Parc les Erables – Bât 1 – 66 route de Sartrouville – BP 49 – 78231 LE PECQ Cedex – France
Tel. : +33 (0)1 34 80 52 00 – Fax : +33 (0)1 30 71 01 89
E-mail : commercial.france@etanco.fr – Web : www.etanco.eu

1. Unique identification code of the product-type :

LR SIL FEU

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Identification of product « batch number »: see packaging of the product

3. Indented use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Sealant for facade for interior application

4. Name, registred trade name or registred trade mark and contract address of the manufacturer as required pursuant to Article 11(5):

LR ETANCO
66 route de Sartrouville – BP49
78231 Le Pecq Cedex
France

5. Where applicable name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2):

Not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

Complain to EN 15651:2012 Type F INT

8. In case of the declaration of performance concerning a construction product for which European Technical Assessment has been issued:

Not relevant

DECLARATION OF PERFORMANCE
N° LRSILFEU 01A EN

9. Declared Performances:

Essential characteristics	Performance	Technical harmonized specification
Fire reaction (According to l'EN 13501-1:2007)	Class E	EN 15651-1:2012
Emissions of dangerous substances	NPD	
Airtightness and waterproofing		
Flow resistance (According to l'EN ISO 7390)	≤ 5 mm	
Loss volume (According to l'EN ISO 10563)	≤ 45 %	
Tensile propriety - Elongation (According to l'EN ISO 8339)	≥ 25 %	
Durability	Pass	
Conditioning : method A Support : • Facade : Aluminum anodized + M2 concrete		

10. The performance of the product identified in points 1 and 2 is in conformity with declared performance in the point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and behalf of the manufacturer by:

Benoit Cheramy Product Manager	Le Pecq – France, 2015-01-09	